


	Commissioning menu - Press and hold 3 seconds		
Display	Description	Units	
r**	Rinse aid setting (e.g. 15 = 1.5mL/L)	0.1 x mL/L	
rP0	Rinse aid prime	0 = Off 1 = On	
d**	Detergent setting (e.g. 33 = 3.3mL/L)	0.1 x mL/L	
dP0	Detergent prime	0 = Off 1 = On	
h**	Water softener setting (if fitted)	°dH	



Errors - E (last 39 logged)

Title

Service menu - Press and hold 6 seconds		
Display	Description	
Р	Program values	
L	Loads	
Е	Errors	
S	Statistics	

Program values - P		
Display	Description	Value
P01	Display wash temperature	***
P02	Display wash level	***
P03	Display rinse temperature	***
P04	Display rinse level	***
P05	Display water flow rate (e.g. 40 = 4.0L/min)	dL/min
P06	Display salt float switch status	0 = Full 1 = Empty
P10	Display door switch status	0 = Open 1 = Closed
P30	Display model type	****
	BOLD - On unpressurised machines only	•

p,	
nnn	New day
E01	Wash tank pressure sensor
E02	Wash tank temperature sensor
E03	Rinse tank pressure sensor
E04	Rinse tank temperature sensor
E05	Wash water level unchanged during cycle.
E06	Rinse water level unchanged during rinse.
E07	Rinse tank temperature not achieved.
E08	Wash tank temperature not achieved.
E09	Wash water level unchanged during soft start.
E10	Salt missing
E11	Display communication failure
E12	Wash tank fill
E13	Rinse tank fill timeout
E14	Door switch
E15	Paddle flow sensor
E16	Wash tank overfill
E17	Filter mesh blocked
E18	Rinse tank temperature exceeded
E19	Wash tank temperature exceeded
E20	Power interruption
E21	EEPROM Error
E22	Invalid machine type
	e machine will enter error mode; this will turn off the nachine and illuminate the cycle indicator red.
	E01 E02 E03 E04 E05 E06 E07 E08 E09 E10 E11 E12 E13 E14 E15 E16 E17 E18 E19 E20 E21 E22 BOLD - th

Display

Statistics - S		
Display	Description	Units
S00	Total number of completed wash cycles	
S01	Total run time (Power connected)	Hours
S02	Total active time (Machine ON)	Hours
S03	Total water usage	Litres
S04	Drain pump failures	
S20	Total number of regenerations	
S21	Total number of cycles without salt	

	BOLD - On unpressurised machines only		
	Loads - l		
Display	Description	Value	
L00	Wash pump	0 = Off 1 = On	
L01	Wash pump + soft start	0 = Off 1 = On	
L02	Wash tank heat element	0 = Off 1 = On	
L03	Detergent pump	0 = Off 1 = On	
L04	Rinse pump	0 = Off 1 = On	
L05	Rinse aid pump	0 = Off 1 = On	
L06	Wash tank heat element - Spare	0 = Off 1 = On	
L07	Rinse tank heat element	0 = Off 1 = On	
L08	Inlet solenoid valve	0 = Off 1 = On	
L09	Drain pump	0 = Off 1 = On	
L11	WS Salt valve	0 = Off 1 = On	
L12	WS Waste valve	0 = Off 1 = On	
L13	WS Waste valve + inlet valve	0 = Off 1 = On	
	BOLD - Safety interlock applies		

Machine base sets	
Base set	Description
1	G350
2	G400
3	G400 Duo
4	G400 Duo WS
5	D400
6	D400 Duo
7	D400 Duo WS
8	G500
9	G500 Duo
10	G500 Duo WS
11	D500
12	D500 Duo
13	D500 Duo WS

Items marked with backgrounds are only present in machines with water softeners fitted.