



**TECHNICAL INFORMATION**

Dimensions	635w x 713d x 1453 - 1999h
Rack Dimension	500 x 500
Clear Entry Height	440
Rinse Water Consumption	3L Per Cycle

WATER CONNECTIONS

Connection Point	3/4 inch (19mm)
Inlet Temperature	60c Max
Flow Rate	11 L/Min
Flow Pressure	2 bar

ELECTRICAL

3 Phase (Standard)	415v 3P 50Hz - 20amp (TCL 6.6Kw)
Single Phase (optional)	240v 1P 50Hz - 15amp (2.6kw)

GENERAL DATA

Weight (Net/Gross)	120Kg / 168Kg
Tank Capacity	28L
Noise Emission	70dB(A)
Cycle Times	1.5 / 3 / 5 / 7 Minute
Theoretical Capacity	720 plates per hour

STANDARD INCLUSIONS

1x 3 Phase Lead
1x 1M Flexible Water Connection Hose
1x 1M Flexible Waste Hose
1x 500 x 500 Flat Cup Basket
1x 500 x 500 Peg Plate Basket
1x 8 Compartment Cutlery Basket

STANDARD FEATURES

- LCD control with digital temperature display
- Integrated drain pump
- Integrated rinse pump
- Integrated chemical pumps
- Dual filtration
- 'Click In & out single piece wash fields
- Made in UK
- Watermark approved
- Bluetooth
- Utensil wash program with optional basket for gastronorm 1/1 trays
- Suitable for straight and corner operation

